



## About HIC Conveyor Rubber Belts


ISO 9001 certified HIC International, 1988 formed company, Delhi based Indian producer of **Continuous Material-Mover**, **Anti-Abrasion Carrying Rubber Belt Conveyor Components**, exporting to industries in Asia, Europe, Africa, Oceania, America to customer's thorough satisfaction.

Full-proof **Quality Assurance Plan** details on: [www.UniversalDelhi.org](http://www.UniversalDelhi.org)

**Credentials** of Quality World-wide Supplies details on: [www.Rubber-Steel-Industrial-Products.com](http://www.Rubber-Steel-Industrial-Products.com)

**Range** of Tailor-made **Conveyor Material-Movement Products** Manufacturing details on: [www.hicRubber.com](http://www.hicRubber.com)

# ANTI-ABRASION CARRYING



Textile Ply as per IS 1891,  
ISO 4195,  
SANS 1173 Open Ends




Chevron V Cleat C15  
Pattern per DIN 22102



Endless Shot Blasting hot  
vulcanized per IS 1891



Conveyor Belt  
Packed Roll



Elevator Belt per AS 4035



**Vendor Data** for Supplier Enlistment information on: [www.hicConveyors.com](http://www.hicConveyors.com)



## Why Choose HIC UNIVERSAL Rubber Belt?

**Super Wear Resistant Textile RMA General Purpose M, N, Z**  
Aids Anti-Abrasion Transport of Stone, Iron Ore, Urea, Bagasse, Pulp

**Superb Bonding Multi-Ply EP, Nylon Fabric SBR Heat Resistant**  
Permits Temp. Up to 150° C Materials Conveying in Smooth & Chevron Pattern

**Excellent Fire Resistant Anti-static Neoprene FRAS**  
Aids Safe Conveying in Underground Coal Mine, Power Station, Sulphur

**Ultra Heat Resistant High Tensile Strength EPDM UHR**  
Allows Hot Temperature Cement Clinker, Ash Handling up to 210° C

**Food Grade Non-Toxic Open and Endless NBR Hygienic**  
Helps Safe Conveying of Sugar, Salt, CTC Tea, Oily Animal Feed, Seafood



### MANUFACTURING RANGE:

Multiply Textile EP and Nylon NN, SHR/FR/MOR/M24/HYGIENIC, 315~2500KN/m Strength, 2~8 Ply, up to 80 inch W, as per IS 1891

Incline Chevron Cleat and Rough Pattern, M24/HR, V-Cleat C15 Profile/Rough-Top up to 1000 mm W, as per DIN 22102



Technical Specifications download from: [www.hic-india.com](http://www.hic-india.com)

RFQ **rubber conveyor belts** specs. As stated below, in English language please, to quote price offer:

1. Width of conveyor rubber belt, mm
2. Ply Tensile Rating EP/NN
3. Rubber Cover Top x Bottom MM
4. Grade
5. Quantity- Open Ends roll lengths in meter or Endless loop length

